



Siamvic

266RC



- Suspension PVC resin

APPLICATIONS

Extrusion

Rigid pipe and profile

CHARACTERISTICS

Siamvic 266RC is a medium K value resin specially designed for rigid PVC extrusion

- very low dust during transportation and pneumatic filling of silos
- high bulk density
- regular feed of extruders as dry blend
- high extrusion output
- easy gelling, good reactivity
- compatibility with a wide range of heat stabilizers and fillers
- low uptake of moisture

Characteristics	Units	Values (*)	Standards
Viscosity index	ml/g	109	ISO 1628-2
K value (cyclohexanone)		66	DIN 53726
Polymerization degree		1000	JIS K6721
Apparent bulk density	kg/l	0.57	ISO 60
Volatile matter	%	≤0.3	ISO 1269
Particle size on 60 mesh (0.250mm)	%	≤5	ISO 1624
on 230 mesh (0.063mm)	%	≥95	

(*) In the case of certain characteristics the values given in this data sheet are means based on a large number of individual measurements distributed around the means in a range corresponding to the normal manufacture and measurement tolerances. These values should not be considered as specifications.

All information in this document is given in good faith but without any warranty or guarantee of any kind whatsoever, whether implied or expressed. Freedom from patent rights must not be assumed. National or local regulation on industrial safety and hygiene are applicable in all cases; in no case can we accept any responsibility for failure to observe such regulations.



บริษัท วินไทย จำกัด (มหาชน)

VINYTHAI PUBLIC COMPANY LIMITED

